

IDM-15V

15" LCD industrial panel monitor with HDMI VGA



Features

- 15" SXGA TFT LCD Panel support 1024 x 768 pixels
- 6mm Aluminum bezel panel with touch screen/strengthen glass
- Rugged construction and modularized design
- VGA + HDMI/DVI + Audio Input signal
- 2 x stereo speakers for industrial automation system voice output
- OSD control keys to optimize the display
- AC 100-240V wide range external ac adapter
- NEMA4 / IP 65 compliant front panel
- Panel mounting or Standard VESA hole (100x100mm)

Specifications

LCD Panel	
Display Type	15" SXGA TFT LCD
Resolution	1024 x 768
Max.color	16.2M
Luminance	250 cd/m2
View Angle	178°(H) , 160°(V)
Pixel Pitch	0.297 x 0.297 mm
Contrast Ratio	700:1
Response Time	5 ms
LCD MTBF	50,000hrs
System	
Touch screen(optional)	Resistive touch screen(RS232/USB)
Input Signals	VGA, HDMI, Audio
Power Supply	100~240VAC, DC12V external ac adapter
DC Power (optional)	DC 9~ 36v input power module

Mechanical and Environmental	
IP level	NEMA4 / IP 65 front panel
Operate temperature	0 °C to 50 °C
Storage temperature	-20 °C to 60 °C
Storage humidity	10% to 90% non-condensing
Anti-Vibration	17HZ-500 HZ 1G PTP
Anti-Shock	1G / peak(11m sec)
Dimensions (WxHxD)	375 x 300 x 42 mm
Weight	Net: 5.0kg , Gross:7.5 kg

Ordering Informations

IDM-15V	15" LCD Industrial Panel Monitor with VGA , HDMI , Audio input
---------	--

Dimensions Diagram

